

Dustproof



Waterproof



IP 68 Rating

Dustproof & Waterproof Fan Series

IP-68

8 : Protection against permanent immersion

6 : Complete protection against dust

■ Application : IT/Telecom · Refrigeration · Outdoor LED Lighting · Solar Inverter

Size (mm)	Model	Voltage (VDC)	Bearing ⊕ 2 BALL	Speed (RPM)	Air Flow (CFM)	Static Pressure (Inch-H2O)	Noise (db(A))	Weight (g)
80x80x25	GF80251B1-0000-AE9	12	⊕	4800	60.0	0.41	47.5	105
	GF80251B2-0000-AE9	12	⊕	4500	57.0	0.35	46.0	105
	GF80251B3-0000-AE9	12	⊕	4200	53.0	0.30	44.5	105
	GE80252B1-0000-AE9	24	⊕	4800	60.0	0.41	47.5	105
	GE80252B2-0000-AE9	24	⊕	4500	57.0	0.35	46.0	105
	GE80252B3-0000-AE9	24	⊕	4200	53.0	0.30	44.5	105
	GE80254B1-0000-AE9	48	⊕	4800	60.0	0.41	47.5	105
	GE80254B2-0000-AE9	48	⊕	4500	57.0	0.35	46.0	105
80x80x32	GF80321B1-0000-AE9	12	⊕	4800	59.4	0.36	45.2	109
	GF80321B2-0000-AE9	12	⊕	4500	55.9	0.32	43.1	109
	GF80321B3-0000-AE9	12	⊕	4100	50.3	0.27	41.1	109
92x92x25	GF92251B1-0000-AE9	12	⊕	4500	75.0	0.35	47.0	113
	GF92251B2-0000-AE9	12	⊕	4200	70.0	0.30	45.0	113
	GF92251B3-0000-AE9	12	⊕	3900	65.0	0.25	43.0	113
	GE92252B1-0000-AE9	24	⊕	4500	75.0	0.35	47.0	113
	GE92252B2-0000-AE9	24	⊕	4200	70.0	0.30	45.0	113
	GE92252B3-0000-AE9	24	⊕	3900	65.0	0.25	43.0	113
	GE92254B1-0000-AE9	48	⊕	4500	75.0	0.35	47.0	113
	GE92254B2-0000-AE9	48	⊕	4200	70.0	0.30	45.0	113
GE92254B3-0000-AE9	48	⊕	3900	65.0	0.25	43.0	113	